

Lenovo
ThinkVision

Smarter
technology
for all

Lenovo

Lenovo ThinkVision T24d-30 Monitor

Crafted to work with you.



**Crafted for
modern workplaces**

Relish the monitor's modern aesthetic with its 4-sided ultra thin bezel design.



**Crafted for
higher productivity**

See more of your content on the screen with its 16:10 aspect ratio and smooth 100 Hz refresh rate.



**Crafted for
supreme comfort**

Work in absolute comfort by adjusting the monitor to your preferred ergonomic position using its LTPS stand.

Lenovo ThinkVision T24d-30 Monitor

Display

Panel Size
24-inch

Screen Dimensions
528.2 mm x 339.6 mm

Panel Type
In-Plane Switching (IPS)

Active Area
518.4 mm x 324.0 mm

Backlight
WLED

Aspect Ratio
16:10

Resolution
1920 x 1200

Pixel Pitch
0.2700 mm x 0.2700 mm

Dot/Pixel Per Inch (DPI/PPI)
94

Viewing Angle (H x V @ CR 10:1)
178° / 178°

Response Time
4ms (Extreme Mode),
6ms (Normal Mode)

Refresh Rate
48 Hz - 100 Hz

Brightness (Typical)
300 cd/m²

Contrast Ratio (Typical)
1500:1

Dynamic Contrast Ratio (Typical)
3M:1

Color Gamut (Coverage Ratio)
99% sRGB (CIE 1931)

Color Support (Typical)
16.7 Million

Color Depth
8-bit¹

Anti-glare
Yes

Connectivity

Video Signal
1 x HDMI 1.4²
1 x DP 1.2
1 x VGA

Audio Signal
1 x Audio Out (3.5 mm)

USB Upstream

1 x USB-B (USB 5Gbps / USB 3.2 Gen 1)³

USB Downstream

4 x USB-A (USB 5Gbps / USB 3.2 Gen 1)³
(1 x BC1.2)

Multimedia

Integrated Speakers
Yes (2 x 2W)

Modular Camera/Speaker Support
Yes (Optional Support⁴)

Special Features

Software

Lenovo ThinkColour
(Lenovo Accessories and
Display Manager)⁵

Natural Low Blue Light
Yes

Power

Power Consumption (Typ. / Max.)
15.0W / 59.4W

Power Consumption Sleep/Off Mode
< 0.5W

Power Consumption Switch-Off Mode
< 0.3W

ENERGYSTAR Power Consumption (Pon / E_{TEC})
12.2W / 38.5kWh

Power Supply
Internal

Voltage Required
AC 100 to 240 V (50-60 Hz)

Mechanical

Tilt Angle (Front / Back)
-5° / 23.5°

Swivel (Left / Right)
-45° / 45°

Lift (Max. Range)
155 mm

Pivot
-90° / 90°

VESA Mount Capability
Yes (100 x 100 mm)

ThinkCentre M Series Tiny Support⁶
Yes, by Tiny Clamp Bracket
Mounting Kit III (PN: 4XF1K72399)

Kensington Lock Slot

Yes (2.5 mm x 6 mm and
3 mm x 7 mm)

Cable Management
Yes

Bezel Color
Raven Black

Bezel Width (Side)
2.0 mm

Bezel Width (Top)
2.0 mm

Bezel Width (Bottom)
11.5 mm

Dimension

Size Packed (W x D x H, mm/inch)
615.0 x 161.0 x 417.0 mm
24.21 x 6.34 x 16.42 inches

Size Unpacked w/ Stand (Highest Position) (W x D x H, mm/inch)
533.0 x 199.7 x 535.7 mm
20.98 x 7.86 x 21.09 inches

Size Unpacked w/ Stand (Lowest Position) (W x D x H, mm/inch)
533.0 x 199.7 x 380.7 mm
20.98 x 7.86 x 14.99 inches

Size Unpacked w/o Stand (Head Only) (W x D x H, mm/inch)
533.0 x 47.8 x 344.3 mm
20.98 x 1.88 x 13.56 inches

Weight Packed (kg / lbs.)
7.84 kg / 17.28 lbs.

Weight Unpacked (kg / lbs.)
5.14 kg / 11.33 lbs.

Weight (Monitor Head Only) (kg / lbs.)
3.16 kg / 6.97 lbs.

What's in the Box

Monitor with Stand
Yes

Power Cable (Cable Length)
1 x Power Cable (1.8 m)

DP Cable (Cable Length)
1 x DP 1.2 Cable (1.8 m)
(Not for PRC Standalone)

HDMI Cable (Cable Length)
1 x HDMI 1.4 Cable (1.8 m)
(Only for PRC)

USB Cable (Cable Length)

1 x USB-B to USB-A Gen 1
Cable (1.8 m, 5Gbps)

Quick Setup Guide
Yes

Certification

ENERGYSTAR Certification
Yes

TCO
9.0

TCO Edge
2.0

EPEAT
Gold

Windows Certification
Windows 10, Windows 11

EU Energy Level Certification
Yes (Level-D)

China Energy Efficiency Standard
Tier 2

TÜV Rheinland Low Blue Light
Yes

TÜV Rheinland Flicker Free
Yes

TÜV Rheinland Low Blue Light (Hardware Solution)
Yes

Eyesafe Display Certification
Yes (Eyesafe 2.0)



¹ Either True 8-bit or 6-bit +FRC. | ² Supports 1920 x 1200 @ 100 Hz as specified in HDMI 1.4. | ³ The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1) 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2) 10 Gbit/s; USB4* 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps) 20 Gbit/s; USB4* 40Gbps (USB 40Gbps) 40 Gbit/s; Thunderbolt™ 3/4: 40 Gbit/s. | ⁴ Compatible with ThinkVision VoIP Stack MC60 Monitor Webcam and MS30 Monitor Soundbar. | ⁵ Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS, Windows On Arm (functions vary across systems). | ⁶ Need to ensemble Tiny Clamp together with the VESA mount to mount the Tiny.

© 2024 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, U.S.A., Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, ThinkVision, and ThinkColour are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others. Specifications may vary depending upon region.