



# ThinkVision T27i-30 Monitor

## Big on comfort. Big on productivity.

Amplify productivity with complete connectivity.

The ThinkVision T27i-30 Monitor is carefully configured with features that deliver better connectivity, enhance your productivity, and ensure your comfort. This large screen 27-inch FHD monitor offers a resolution of 1920 x 1080 pixels with a wide viewing angle for clear, crisp on-screen content. Expect rich, vibrant colors with 99% sRGB that sharpens the display and is great for video producers and film animators. Long hours at the screen can cause eye fatigue but not with the ThinkVision T27i-30 Monitor which has Natural Low Blue Light technology that cuts down harmful blue light to give your eyes a comfortable, strain-free experience. The monitor hosts a range of versatile connectors for extended usage with VGA, HDMI 2.1<sup>1</sup>, DP 1.2 ports and a USB Hub. Say hello to great video conferencing<sup>2</sup> capabilities as with this monitor's expandable functions. A full-function ergonomic stand allows for greater flexibility, with a wider adjustment range and low head position so you can set up the monitor to suit your comfort. What's more, you'll be delighted to know that the ThinkVision T27i-30 Monitor comes in an eco-friendly paper-pulp packaging that's great for the environment.

## KEY FEATURES OF THINKVISION T27i-30 MONITOR



### A treat for your eyes

The ThinkVision T27i-30 Monitor's IPS display is a treat for your eyes with an ultra-wide viewing angle that delivers high color accuracy and image quality. This large 27-inch monitor feels even bigger with 3-side NearEdgeless bezels. Rich display quality is enhanced with 99% sRGB color for an impressive viewing experience. Comfort is key with the ThinkVision T27i-30 Monitor with Natural Low Blue Light technology which helps to minimize visual fatigue and strain, so your eyes are protected.



### Plug in to productivity

You won't miss a beat with the ThinkVision T27i-30 Monitor. A range of connectivity options from VGA and HDMI 2.1<sup>1</sup> ports to DP 1.2 ports ensure you're always ready to plug in and perform. Take advantage of the monitor's four USB 3.2 Gen 1<sup>3</sup> ports for easy extension of USB devices. A dedicated USB port for modular VoIP solution - ThinkVision MC30 Monitor Soundbar and ThinkVision MC60 Monitor Webcam<sup>2</sup> enables incredible video conferencing experiences. Enjoy easy and effortless access to configuration settings with the updated ThinkColour software (Lenovo Accessories and Display Manager)<sup>4</sup>. The ThinkVision T27i-30 is geared to ensure incredible connectivity that amplifies your productivity.

USB Type-A



### User-friendly and eco-friendly

Enjoy an upgraded user experience that makes comfort and ease a priority with the ThinkVision T27i-30 Monitor. Save space and reduce clutter with cleaner cable management. Joystick control puts easy control at your fingertips. A full-function ergonomic stand with wider adjustable ranges including lift range and tilt ensure that you can position the monitor perfectly for your comfort. ThinkVision T27i-30 Monitor also supports cableless modular VoIP solution<sup>2</sup> and a phone holder for enhanced flexibility. It is also eco-friendly with sustainable paper pulp packaging that's great for the environment!

<sup>1</sup> Supports 1920 x 1080 @ 60Hz as specified in HDMI 2.1. | <sup>2</sup> Modular VoIP solution (ThinkVision MC30 Monitor Soundbar and ThinkVision MC60 Monitor Webcam) is sold separately. | <sup>3</sup> Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: 5 Gbit/s for USB 3.2 Gen 1; 10 Gbit/s for USB 3.2 Gen 2 & 20 Gbit/s for USB 3.2 Gen2x2. | <sup>4</sup> Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS, Windows On Arm (functions vary across systems).

# ThinkVision T27i-30 Monitor

## DISPLAY

**Panel Size**  
27-inch

**Screen Dimensions**  
607.1 mm x 354.1 mm

**Panel Type**  
3-side NearEdgeless In-Plane Switching

**Active Area**  
597.9 mm x 336.3 mm

**Backlight**  
WLED

**Aspect Ratio**  
16:9

**Resolution**  
1920 x 1080

**Pixel Pitch**  
0.311 mm x 0.311 mm

**Dot/Pixel Per Inch (DPI/PPI)**  
81

**Viewing Angle (H x V @ CR 10:1)**  
178° / 178°

**Response Time**  
4ms (Extreme Mode),  
6ms (Normal Mode)

**Refresh Rate**  
60Hz

**Brightness (Typical)**  
300 cd/m<sup>2</sup>

**Contrast Ratio (Typical)**  
1000:1

**Dynamic Contrast Ratio (Typical)**  
3M:1

**Color Gamut (Coverage Ratio)**  
99% sRGB (CIE 1931)

**Color Support (Typical)**  
16.7 Million

**Color Depth**  
8-bit (6+FRC)

**Anti-Glare**  
Yes

## CONNECTIVITY

**Video Signal**  
1 x HDMI 2.1<sup>1</sup>  
1 x DP 1.2  
1 x VGA

**Audio Signal**  
1 x Audio Out (3.5 mm)

**USB Hub**  
Yes

**USB Upstream**  
1 x USB 3.2 Gen 1<sup>2</sup> (by USB Type-B)

**USB Downstream**  
4 x USB 3.2 Gen1<sup>2</sup> (1 x BC 1.2)

## MULTIMEDIA

**Modular Camera/Speaker Support**  
Yes (Optional Support<sup>3</sup>)

## SPECIAL FEATURES

**Software**  
Lenovo ThinkColour  
(Lenovo Accessories and  
Display Manager)<sup>4</sup>

**Natural Low Blue Light**  
Yes

## POWER

**Power Consumption (Typ. / Max.)**  
24W / 65W

**Power Consumption Sleep/Off Mode**  
< 0.5W

**Power Consumption Switch-Off Mode**  
< 0.3W

**ENERGY STAR Power Consumption  
(Pon/E<sub>TEC</sub>)**  
15W / 50kWh

**Power Supply**  
Internal

**Voltage Required**  
AC 100 to 240 V (50-60 Hz)

## MECHANICAL

**Tilt Angle (Front / Back)**  
-5° / 23.5°

**Swivel Angle (Left / Right)**  
+45° / -45°

**Lift Range**  
155 mm

**Pivot**  
-90° / 90°

**VESA Mount Capability**  
Yes (100 x 100 mm)

**ThinkCentre M Series Tiny Support**  
Yes, by Tiny Clamp Bracket  
Mounting Kit III (PN: 4XFIK72399)<sup>5</sup>

**Kensington Lock Slot**  
Yes (2.5 mm x 6 mm and 3 mm x 7 mm)

**Cable Management**  
Yes

**Bezel Color**  
Raven Black

**Bezel Width (Side)**  
2.0 mm

**Bezel Width (Top / Bottom)**  
2.0 / 17.6 mm

## DIMENSION

**Size Packed  
(D x H x W) (mm/inch)**  
525.0 x 148.0 x 690.0 mm  
20.67 x 5.83 x 21.17 inches

**Size Unpacked w/ Stand  
(Lowest Position)  
(D x H x W) (mm/inch)**  
204.5 x 389.3 x 611.9 mm  
8.05 x 15.33 x 24.09 inches

**Size Unpacked w/ Stand  
(Highest Position)  
(D x H x W) (mm/inch)**  
204.5 x 544.3 x 611.9 mm  
8.05 x 21.43 x 24.09 inches

**Size Unpacked w/o Stand  
(Head Only)  
(D x H x W) (mm/inch)**  
50.0 x 362.5 x 611.9 mm  
1.97 x 14.27 x 24.09 inches

**Weight Packed (kg / lb)**  
10.1 kg / 22.3 lbs.

**Weight Unpacked (kg / lb)**  
6.9 kg / 15.2 lbs.

**Weight (Monitor Head Only) (kg / lb)**  
4.9 kg / 10.8 lbs.

## WHAT'S IN THE BOX

**Monitor with Stand**  
Yes

**Power Cable (Cable Length)**  
1 x Power Cable (1.8m)

**DP Cable (Cable Length)**  
1 x DP 1.2 Cable (1.8m)

**HDMI Cable (Cable Length)**  
1 x HDMI 1.4 Cable  
(1.8m, For Brazil only)

**USB Cable (Cable Length)**  
1 x USB Type-A to Type-B Cable (1.8m)

**Quick Setup Guide**  
Yes

## CERTIFICATION

**ENERGY STAR Certification**  
Yes

**CCC**  
Yes

**TCO**  
9.0

**TCO Edge**  
2.0

**EPEAT**  
Gold

**Volatile Organic Compound Certification**  
Yes

**RoHS (2011/65/EU)**  
Yes

**Windows Certification**  
Windows 10, Windows 11

**China Energy Efficiency Standard**  
Grade 2

**TÜV Rheinland Eye Comfort**  
Yes

**TÜV Low Blue Light  
(Hardware Solution)**  
Yes

**Eyesafe Display Certification**  
Yes



<sup>1</sup> Supports 1920 x 1080 @ 60Hz as specified in HDMI 2.1. | <sup>2</sup> Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: 5 Gbit/s for USB 3.2 Gen 1; 10 Gbit/s for USB 3.2 Gen 2 & 20 Gbit/s for USB 3.2 Gen2x2. | <sup>3</sup> Modular VoIP solution (ThinkVision MC30 Monitor Soundbar and ThinkVision MC60 Monitor Webcam) is sold separately. | <sup>4</sup> Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS, Windows On Arm (functions vary across systems). | <sup>5</sup> Sold separately.

© 2023 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, U.S.A., Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, ThinkVision, and ThinkColour are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.

Specifications may vary depending upon region.