

## **PERFORMANCE**

#### **Panel**

**Panel** 

In-Plane Switching (IPS)

**Display Size** 

23.8 inches (604.7mm)

**Max View Area** 

WxH: 527 x 296.5 mm (20.75 x 11.67 inches)

**Native Resolution** 

1920x1080

**Aspect Ratio** 

16:9

**Pixel Pitch** 

0.2745 x 0.2745 mm

DPI

92.6 dpi

**Brightness** 

250 nits

**Contrast Ratio** 

1000:1

**Pixel Response Time** 

4 ms (extreme mode) / 6 ms (typical mode) / 14 ms (off mode)

**Color Gamut** 

72% NTSC

**Viewing Angle** 

Horizontal: +/- 89°, vertical: +/- 89°

**Anti-glare** 

Anti-glare

#### Multi-Media

Camera

1080p, with dual microphone and LED indicator

Microphone

Dual array microphone

**Speakers** 

Stereo speakers, 2W x2

## **Power Supply**

#### **Power Supply**

Power	Туре	Efficiency	Key Features
90W	Adapter	88%	-

#### **Power Consumption**

19 watts typical, 32 watts max

## **DESIGN**

## Menu

## **Presets and User Settings**

• Presets: 25



• User settings: 25

#### On Screen Display

On screen display with digital user controls (8 languages)

## **Display**

## Touchscreen

(Optional)10-point multi-touch, supports Wake on Touch. ONLY for model 10QXPAT1 and 10QXPAR1.

#### Mechanical

### **Compatible Tiny**

 $P330 \ / \ P320 \ / \ M920(x) \ / \ M720 \ / \ M910(x) \ / \ M710 \ / \ M900(x) \ / \ M700 \ / \ M630e \ / \ M625 \ / \ M600 \ / \ M75q \ / \ M715 \ / \ M93p \ / \ M83 \ / \ M73 \ / \ M53 \ / \ Chromebox \ Tiny$ 

#### **Bezel Width**

Top / side: 2mmBottom: 22.1mm

#### **Buttons**

- · Volume button
- Power button
- Exit button
- Menu button
- · Mode-switching button
- · Brightness button

#### Cables

Undetachable 3-in-1 cable (power connector, USB [supports USB 3.1 Gen 1 / USB 2.0], DisplayPort™)

#### **Case Color**

Black

#### Dimensions (WxDxH)

Models	Dimensions	
Models with full function monitor stand	539.8 x 282.3 x 509.4 mm (21.25 x 11.11 x 20.06 inches)	
Models without stand	539.8 x 72.5 x 367.6 mm (21.25 x 2.85 x 14.47 inches)	

#### Weight

Models	Weight
Models without stand	3.61 kg (7.96 lbs)
Models with full function monitor stand	5.86 kg (12.92 lbs)

#### Mounting

Supports VESA mount 100mm

#### Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 110mm lift, 0° to +90° pivot

#### In the Box

- TIO 24 (monitor)
- Detachable stand
- Driver CD
- · Power adapter
- Power cord
- Quick start and safety poster
- User's guide

## CONNECTIVITY

## **Ports**

#### **Rear Ports**

- 1x USB upstream port
- 1x DisplayPort

# ThinkCentre Tiny-In-One 24 Gen 3



• 1x power connector

#### Left Ports[1]

- 1x USB 3.1 Gen 1 (on TIO)
- · Side ports offered by installed Tiny (on Tiny)

#### Notes:

1. The availability and version depends on the Tiny installed or the PC connected via USB upstream port

## **SERVICE**

## **Warranty**

#### **Base Warranty**

3-year carry-in or courier service

## **CERTIFICATIONS**

#### **Green Certifications**

## **Green Certifications**

- EPEAT™ Silver
- ENERGY STAR® 8.0
- TCO Certified 7.0
- TCO edge 2.0
- TUV
- ULE Gold
- · RoHS compliant
- VOC
- WEEE

## **Other Certifications**

## **Other Certifications**

- FCC Class B
- ISO 9241-307
- TÜV Rheinland Eye Comfort Certification













