

ThinkVision T24i-19 MONITOR



SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D)	
Panel Size	23.8" Wide	Size Packed (mm)	422 x 622 x 190
Panel Type	In-Plane-Switching	(inches)	16.61" x 24.48" x 7.48"
Backlight	WLED	Size Unpacked with Stand Lowest Position (mm)	540.2 x 261.75 x 373.4
Resolution	FHD (1920 x 1080)	(inches)	21.26" x 10.3" x 14.7"
Aspect Ratio	16:9	Highest Position (mm)	540.2 x 261.75 x 483.4
Anti-Glare	Yes	(inches)	21.26" x 10.3" x 19"
Near Edgeless Screen	Yes	Size Unpacked without Stand (Monitor Head Only) (mm)	540.2 x 46.45 x 325.98
Screen Dimensions (W x H) (mm)	527.04 x 296.46	(inches)	21.26" x 1.82" x 12.83"
(inches)	20.75" x 11.67"	Stand Base Footprint Area (mm)	250 x 250
Brightness	250 nits	(inches)	9.84" x 9.84"
Viewing Angle (H/V at CR 10:1)	178°/178°	Weight Packed	Starting at 16.39 lbs (7.45 kg)
Contrast Ratio (Typical)	1000:1	Unpacked	Starting at 11.33 lbs (5.15 kg)
Dynamic Contrast Ratio	3M:1	Monitor Head Only	Starting at 7.26 lbs (3.3 kg)
Speakers	2 x 2W	Full Container Load (40' STD / 20' STD)	1140 / 540 Units
Pixel Pitch (mm)	0.2745 x 0.2745		
Color Gamut (CIE 1931)	72% NTSC		
Color Depth	8 bit		
Color Support (Typical)	16.7 Million		
Response Time (GtG)	4 ms / 6 ms		
OSD Controls			
Buttons	5		
Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian		
CONNECTIVITY		POWER CONSUMPTION	
Video Input Signals	VGA + HDMI + DisplayPort	Typical	16.5 W
Video Cables Supplied	VGA, DisplayPort, USB, Power, HDMI (for NA only)	Maximum	59 W
USB Hub	USB 3.0 ¹ (4 x down, 1 x BC)	Sleep-Mode	<0.5 W
Audio Out	Yes (3.5 mm)	Switch Off-Mode	<0.3 W
Power	Internal	Power Supply	Internal
Soundbar Support*	Yes	Power Voltage	90 VAC – 264 VAC
		ENERGY STAR (P _{on})	13.67 W
		ENERGY STAR (E _{TEC})	43.51 kWh
MECHANICAL		WHAT'S IN THE BOX	
Tilt Angle (Front / Back)	-5° / 30°	Monitor with Stand	
Swivel Angle (Left / Right)	+/-45°	1 x Power Cable	
Lift Range (mm)	110	1 x VGA Cable	
Pivot	+/-90°	1 x DisplayPort - DisplayPort Cable	
Stand	LTPS	1 x HDMI Cable (NA Only)	
Cable Management	Yes	Quick Setup Guide	
Kensington Lock	Yes		
VESA Mount (mm x mm)	Yes (100 X 100)		
Bezel Color	Raven Black		
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Sides (mm / inches)	2 / 0.08"		
		CERTIFICATIONS	
		EPEAT	Silver
		ENERGY STAR Rating	8.0
		TCO	7.0
		TCO Edge	2.0
		ULE	Gold
		RoHS (EU 2002/95/EC)	Yes
		China Energy Efficiency Standard	Tier 2
		Windows Certification	Windows 7 / Windows 10
		TÜV Eye Comfort Certification	Yes
		TINY Support	Yes

* Optional.

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: ~ 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



WWW.LENOVO.COM