

ThinkVision T24m-10 MONITOR

SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size	23.8"	Size Packed (mm)	422 x 622 x 190
Panel Type	In-Plane Switching	(inches)	16.61" x 24.48" x 7.48"
Backlight	WLED	Size Unpacked with Stand	
Resolution	1920 x 1080	Lowest Position (mm)	540.2 x 261.75 x 373.4
Aspect Ratio	16:9	(inches)	21.26" x 10.3" x 14.7"
Anti-Glare	Yes	Highest Position (mm)	540.2 x 261.75 x 483.4
Screen Dimensions (W x H) (mm)	527.04 (H) x 296.46 (V)	(inches)	21.26" x 10.3" x 19"
Maximum Brightness (Typical)	250 cd/m ²	Size Unpacked without Stand (Monitor Head Only) (mm)	540.2 x 46.45 x 325.98
Viewing Angle (H/V at CR 10:1)	178°/178°	(inches)	21.26" x 1.82" x 12.83"
Contrast Ratio (Typical)	1000:1	Distance from Table to Panel	
Dynamic Contrast Ratio (Typical)	3M:1	Lowest Pixel at Bottom of Screen (mm / inches)	70.37 / 2.77"
Pixel Pitch (mm)	0.2745 (H) x 0.2745 (V)	Highest Pixel at Top of Screen (mm / inches)	476.8 / 18.77"
Dot/Pixel Per Inch (DPI/PPI)	92	Stand Base Footprint Area (mm / inches)	250 x 250 / 9.84" x 9.84"
Color Gamut (CIE 1931)	72% NTSC	Weight	
Response Time (gray to gray)	4 ms (Extreme mode) 6 ms (Normal mode)	Packed	Starting at 16.39 lbs (7.45 kg)
		Unpacked	Starting at 11.33 lbs (5.15 kg)
		Monitor Head Only	Starting at 7.26 lbs (3.3 kg)
		Full Container Load (40' STD / 20' STD)	1140 / 540 Units
POWER CONSUMPTION		SPECIAL FEATURES	
Typical	19 W	Thin Client Support (Tiny)	Yes (by Tiny Clamp Bracket Kit + VESA Mount)
Maximum	116 W		
Sleep-Mode	<0.5 W		
Switch Off-Mode	<0.5 W		
Power Supply	Internal		
Power Voltage	90 VAC - 264 VAC		
Voltage Dynamic Frequency	47 Hz - 63 Hz		
CONNECTIVITY		WHAT'S IN THE BOX	
Video Input Signals	HDMI 1.4 + DisplayPort 1.2a + USB Type-C	Monitor with Stand	
Video Cables Supplied	USB Type-C to Type-C Cable	1 x Power Cable	
Video Cable Length	1.8 m	1 x USB Type-C™ to Type-C™ Cable	
USB Hub	Yes 1 x USB 3.0 ¹ (Upstream, by USB Type-C) 4 x USB 3.0 ¹ (Downstream, incl. 1BC)	Quick Setup Guide	
Audio-Out	Yes (3.5 mm)		
MECHANICAL		CERTIFICATIONS	
Tilt Angle (Front / Back)	-5° / 30°	EPEAT	Silver
Swivel Angle (Left / Right)	+/-45°	ENERGY STAR Rating	8.0
Lift Range (mm)	110	ULE	Gold
Pivot	+/-90°	TCO	TCO 7.0 / TCO Edge 2.0
VESA Mount (mm x mm)	Yes (100 x 100)	RoHS (EU 2002/95/EC)	Yes
Kensington Lock Slot	Yes	Windows Certification	Windows 7 / Windows 10
Cable Management	Yes	China Energy Efficiency Standard	Tier 2
Bezel Color	Raven Black	TÜV Eye Comfort Certification	Yes
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Sides (mm / inches)	2 / 0.08"		

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



WWW.LENOVO.COM

