

PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core i5-11400H	6	12	2.7GHz	4.5GHz	12MB	Intel UHD Graphics
Core i7-11800H	8	16	2.3GHz	4.6GHz	24MB	Intel UHD Graphics

Operating System

Operating System**

- Windows® 10 Home 64
- Windows 10 Home 64 Single Language
- Windows 10 Pro 64
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 Pro
- No operating system

Graphics

Graphics**

Graphics	Type	Memory	Boost Clock	TGP	Key Features
NVIDIA® GeForce RTX™ 3050 Laptop GPU	Discrete	4GB GDDR6	1500 MHz / 1740 MHz	95W	Advanced Optimus, Resizable BAR, Dynamic Boost 2.0, DirectX® 12 Ultimate
NVIDIA GeForce RTX 3050 Ti Laptop GPU	Discrete	4GB GDDR6	1485 MHz / 1695 MHz	95W	Advanced Optimus, Resizable BAR, Dynamic Boost 2.0, DirectX 12 Ultimate

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI supports up to 7680x4320@60Hz
- USB-C supports up to 5120x3200@60Hz

Chipset

Chipset

Intel HM570 chipset

Memory

Max Memory^[1]

Up to 16GB DDR4-3200 offering

Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

^[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support^[1]

Up to two drives, 1x 2.5" HDD + 1x M.2 SSD

- 2.5" HDD up to 1TB
- M.2 2242 SSD up to 512GB
- M.2 2280 SSD up to 1TB

Storage Slot

- HDD/SSD mode: one 2.5" drive slot + one M.2 slot
 - One 2.5" SATA HDD slot
 - One M.2 2280 PCIe® 3.0 x4 slot
- Dual SSD mode: two M.2 slots
 - Two M.2 2280 PCIe 3.0 x4 slot

Storage Type***

Disk Type	Interface	RPM	Offering
2.5" SATA HDD	SATA 6Gb/s	5.4K	1TB
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4	-	256GB / 512GB
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo storage offerings.

Removable Storage

Optical

None

Card Reader

2-in-1 card reader (SD, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

Stereo speakers, 2W x2, Nahimic Audio

Microphone

Dual-microphone array

Camera

HD 720p, with camera shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 80Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life^[1]

MobileMark® 2018: 7.5 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

230W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect	Contrast	Color	Refresh	Viewing	Key
------	------------	-------	------	------------	---------	--------	----------	-------	---------	---------	-----

						Ratio	Ratio	Gamut	Rate	Angle (L/R/U/D)	Features
17.3"	FHD (1920x1080)	None	IPS	300nits	Anti-glare	16:9	800:1	72% NTSC	60Hz	85°/85°/-/-	DC dimmer
17.3"	FHD (1920x1080)	None	IPS	300nits	Anti-glare	16:9	800:1	72% NTSC	144Hz	85°/85°/-/-	Dolby® Vision™, DC dimmer

Touchscreen

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

White backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, 69 x 104 mm (2.72 x 4.09 inches)

Mechanical

Dimensions (WxDxH)^[1]

398.6 x 290 x 24.3-26.2 mm (15.7 x 11.41 x 0.96-1.03 inches)

Weight^[2]

Around 2.98 kg (6.57 lbs)

Case Color

Phantom blue (top), shadow black (bottom)

Surface Treatment

Painting

Case Material

PC-ABS (top), PC-ABS (bottom)

System Lighting

No system lighting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet^[1]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth®^{[2][3]}

Wi-Fi® 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card

Notes:

[1] Wake-on-LAN needs the power adapter plugged in.

[2] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

[3] Wi-Fi 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 1x Card reader
- 1x Ethernet (RJ-45)
- 1x HDMI 2.1
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector
- 1x Thunderbolt™ 4 / USB4® 40Gbps (support data transfer and DisplayPort™ 1.4)
- 1x Thunderbolt 4 / USB4 40Gbps (support data transfer, Power Delivery and DisplayPort 1.4)
- 1x USB 3.2 Gen 1 (Always On)
- 3x USB 3.2 Gen 1

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt 3/4: 40 Gbit/s.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

No fingerprint reader

BIOS Security

- Power-on password
- Supervisor password
- Hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories

None

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- ErP Lot 3
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.