

OVERVIEW



1. USB 3.2 Gen 1	5. USB 3.2 Gen 1			
2. HDMI 1.4b	6. Headphone / microphone combo jack (3.5mm)			
3. Kensington Nano Security Slot	7. microSD card reader			
4. USB-C 3.2 Gen 1				



PERFORMANCE

Processor

Processor Family

Intel® Celeron® Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Celeron® N4500	Celeron® N4500 2 2		1.1GHz	2.8GHz	4MB L3	Intel® UHD Graphics
Celeron® N5100	4	4	1.1GHz	2.8GHz	4MB L3	Intel® UHD Graphics

Operating System

Operating System

ChromeOS

Graphics

Graphics

Graphics	Туре	Memory	Key Features
Intel® UHD Graphics	Integrated	Shared	DirectX® 12

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4K@30Hz
- USB-C® supports up to 4K@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type[1]

LPDDR4x-2933

Notes:

[1] Installed memory is actually 4266MHz but may run at 2933MHz depending on the memory support capability of processor.

Storage

Storage Support[1]

- 32GB eMMC 5.1 on systemboard
- 64GB eMMC 5.1 on systemboard

Storage Slot

eMMC on systemboard, no slots

Storage Type

Disk Type	Interface	Offering		
Flash Memory	eMMC 5.1	32GB / 64GB		

Notes:



[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Optical

None

Card Reader

3-in-1 microSD card reader (SD, SDHC, SDXC)

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC5682I-VD codec

Speakers

Stereo speakers, 2W x2

Microphone

Single microphone

Camera

HD 720p, with privacy shutter, fixed focus

Sensor

Sensors

Hall sensor

Battery

Battery

Integrated Li-Polymer 42Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life[1]

Google power load test: 11.9 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 45W USB-C[®] (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C[®] (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display

Si	ze	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)
11	6"	HD (1366x768)	None	TN	250nits	Anti- glare	16:9	400:1	45% NTSC	45°/45°/15°/35°

Touchscreen

Non-touch



Input Device

Keyboard

Chrome keyboard, 6-row, spill-resistant

Keyboard Backlight

Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 60.5 x 104 mm (2.38 x 4.09 inches)

Mechanical

Dimensions (WxDxH)[1]

289.6 x 202 x 19.9 mm (11.4 x 7.95 x 0.78 inches)

Weight^[2]

Around 1.21 kg (2.67 lbs)

Case Color

Grev

Surface Treatment

Texture

Case Material

PC-ABS covered with rubber bumper (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**

- Realtek® RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.3 hardware ready), M.2 card[1]
- Intel® Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1 (Bluetooth® 5.2 hardware ready), M.2 Card[2]

Notes:

[1] Bluetooth® 5.3 is hardware ready but may run at a lower version due to OS limitations.

Wi-Fi® 6 full features might be limited by country-level restrictions.

[2] Wi-Fi® 6 full features might be limited by country-level restrictions.

Bluetooth® 5.2 is hardware ready but may run at a lower version due to OS limitations.

Ports^[1]

Standard Ports

- 2x USB 3.2 Gen 1
- 1x USB-C® 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.2)
- 1x HDMI® 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x microSD card reader

Notes

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;



USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s; USB4 $^{\circ}$ 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s; USB4 $^{\circ}$ 40Gbps (USB 40Gbps): 40 Gbit/s; Thunderbolt $^{\top}$ 3/4: 40 Gbit/s.

Docking

Docking

Various docking solutions supported via Thunderbolt™ or USB-C®. For more compatible docking solutions, please visit <u>Docking for Lenovo® 100e Chromebook Gen 3</u>

SECURITY & PRIVACY

Security

Security Chip

Google Security Chip H1

Physical Locks

Kensington® Nano Security Slot™

Fingerprint Reader

No fingerprint reader

BIOS Security

No support

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year mail-in service
- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service

ENVIRONMENTAL

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]



None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for Lenovo® 100e Chromebook Gen 3.

CERTIFICATIONS

Green Certifications⁽¹⁾

Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Silver Registered[3]
- ErP Lot 3
- RoHS compliant
- TCO Certified

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please see epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













