OVERVIEW



1. HDMI	5. E-shutter switch
2. USB-C (USB 5Gbps), with USB PD 3.0 & DP 1.2	6. Headphone / microphone combo jack (3.5mm)
3. Thunderbolt 4	7. USB-A (USB 5Gbps)
4. SD card reader	8. USB-A (USB 5Gbps), Always On

Lenovo Slim Pro 9 14IRP8

PERFORMANCE

Processor

Processor Family

13th Generation Intel® H Series Core i7 / i9 Processor

Processor

Processor Cores Threads		Base Frequency	Max Frequency	Cache	Processor Graphics	
Core i7- 13705H	14 (6 P-core + 8 E-core)	20	P-core 2.4GHz / E-core 1.8GHz	P-core 5.0GHz / E-core 3.7GHz	24MB	Intel® Iris® Xe Graphics

Operating System

- Operating System**
- Windows® 11 Pro
- Windows® 11 Home
- Windows[®] 11 Home Single Language

Graphics

Graphics

Graphics	Туре	Memory	Boost Clock	TGP	
NVIDIA® GeForce RTX™ 4050 Laptop GPU	Discrete	6GB GDDR6	2355 MHz	80W	Advanced Optimus, Dynamic Boost 2.0, DirectX® 12 Ultimate

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C® and Thunderbolt™)

• HDMI $^{\scriptscriptstyle \otimes}$ supports up to 7680x4320@60Hz

• USB-C[®] supports up to 3840x2160@60Hz

Thunderbolt[™] supports up to 7680x4320@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5x-6400

Storage

Storage Support^[1]

One drive, up to 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe[®] 4.0 x4 slot

Storage Type

Disk Type	Interface	Offering
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

4 stereo speakers, 2W x2 (woofers), 1W x2 (tweeters), optimized with Dolby Atmos®, Smart Amplifier (AMP)

Microphone

Quad-microphone array

Camera

5.0MP + IR, with E-shutter, fixed focus

Sensor

Sensors

- Ambient light sensor (ALS)
- Hall sensor
- ToF sensor

Battery

Battery

Integrated Li-Polymer 75Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)^[1]

Max Battery Life^[2]

MobileMark® 2018@200nits: 7.58 hr Local video (1080p) playback@150nits: 10.12 hr

Notes:

[1] Rapid Charge Pro is only effective in hibernates or fully shutting down the computer.

[2] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter^[1]

140W USB-C[®] slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display

Siz	e Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14.	5″ 3K (3072x1920)	OGM touch	Mini LED	1,200nits	Glossy, anti- fingerprint	16:10	1,000,000:1	100% P3, 100% Adobe® RGB, 100% sRGB	165Hz (Max)	89°/89°/89°/89°	∆E<1 (Avg.), Eyesafe® Certified 2.0, Dolby Vision®, VESA DisplayHDR™

										1000, Glass, TCON
--	--	--	--	--	--	--	--	--	--	----------------------

Color Calibration

TCON (Timing Controller) color calibration

Touchscreen

OGM (One Glass Metal mesh) multi-touch, supports 10-point touch

Input Device

Keyboard

6-row, multimedia Fn keys

Keyboard Backlight

LED backlight

Touchpad

Buttonless glass surface multi-touch touchpad, supports Precision TouchPad (PTP), 80 x 135 mm (3.15 x 5.31 inches)

Mechanical

Dimensions (WxDxH)^[1]

326.95 x 223.54 x 17.6 mm (12.87 x 8.80 x 0.69 inches)

Weight^[2]

Starting at 1.68 kg (3.70 lbs)

Case Color

Storm grey

Surface Treatment

Aluminium stamping (anodized with sandblasting)

Case Material

Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet No onboard Ethernet

WLAN + Bluetooth®[1]

Wi-Fi[®] 6E, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.3, M.2 card

Notes:

[1] Wi-Fi[®] 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth[®] 5.3 operation requires Windows[®] 11. For more information please visit <u>General Bluetooth[®] Support Information</u> <u>on Microsoft[®]</u>.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C[®] (USB 5Gbps / USB 3.2 Gen 1), with USB PD 3.0 and DisplayPort[™] 1.2
- 1x USB-C[®] (Thunderbolt[™] 4 / USB4[®] 40Gbps), with USB PD 3.0 and DisplayPort[™] 1.4

- 1x HDMI[®] 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x SD card reader

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions are supported via Thunderbolt™ / USB-C[®]. For more compatible docking solutions, please visit <u>Docking for Lenovo[®] Slim Pro 9 14IRP8</u>

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- User password
- User hard disk passwordMaster hard disk password
- Master hard disk passy
 Self-healing BIOS
- Self-healing BIOS

Other Security

- IR camera for Windows® Hello (facial recognition)
- E-shutter

SERVICE

Warranty

Base Warranty 1-year courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for Lenovo® Slim Pro 9 14IRP8.

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Lenovo Slim Pro 9 14IRP8

Lenovo

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material

FSC-certificated Paper used in Box, Cushion, and Manual
50% Recycled Aluminum on D Cover
30% PCC Recycled Plastic used in Adapter
25% PCC Recycled Plastic used in Battery Pack
30% PCC Recycled Plastic used in Speaker Enclosure
65% PCC Recycled Plastic used in Keyboard
97% PIC Recycled Plastic used in Cushion

CERTIFICATIONS

Green Certifications^{III}

Green Certifications^[2]

- ENERGY STAR[®] 8.0
- EPEAT[™] Gold Registered^[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.
 [2] EPEAT[™] registration and ENERGY STAR[®] certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT[™] is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed (21 test items)

Other Certifications

- Intel[®] Evo[™] Platform
- Eyesafe® Certified 2.0
- TÜV Rheinland[®] Low Blue Light (Hardware Solution)

• Feature with ** means that only one offering listed under the feature is configured on selected models.

Lenovo reserves the right to change specifications or other product information without
notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES
THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING
THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some
jurisdictions do not allow disclaimer of express or implied warranties in certain

transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.



intel

intel



intel

intel