


# **OVERVIEW**





1. Power connector	5. Headphone / microphone combo jack (3.5mm)
2. USB 3.2 Gen 1	6. Ethernet (RJ-45)
3. HDMI	7. USB 2.0
4. USB-C 3.2 Gen 1	8. Kensington Nano Security Slot



# **PERFORMANCE**

### **Processor**

#### **Processor Family**

13th Generation Intel® U or H Series Core i3 / i5 / i7 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core i3-1315U	6 (2 P-core + 4 E-core)	8	P-core 1.2GHz / E-core 0.9GHz	P-core 4.5GHz / E-core 3.3GHz	10MB	Intel® UHD Graphics
Core i5-1335U	10 (2 P-core + 8 E-core)		P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics[1]
Core i5- 13420H	8 (4 P-core + 4 E-core)	12	P-core 2.1GHz / E-core 1.5GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® UHD Graphics
Core i7-1355U	10 (2 P-core + 8 E-core)	12	P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz		Intel® Iris® Xe Graphics <sup>[2]</sup>
Core i7- 13620H	10 (6 P-core + 4 E-core)	16	P-core 2.4GHz / E-core 1.8GHz	P-core 4.9GHz / E-core 3.6GHz	24MB	Intel® UHD Graphics

#### Notes:

[1], [2] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

# **Operating System**

### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- · No preload operating system

### **Graphics**

### Graphics\*\*

Graphics	Type	Memory	TGP	Key Features
Intel® UHD Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12.1
Intel® Iris® Xe Graphics[1]	Integrated	Shared	Share CPU TDP	DirectX® 12.1

#### Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

# **Monitor Support**

### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 4096x2160@30Hz
- USB-C® supports up to 4096x2160@60Hz

# **Chipset**

#### Chipset

Intel® SoC (System on Chip) platform

# **Memory**

### Max Memory[1]

• Up to 16GB (16GB soldered + empty SO-DIMM slot) DDR4-2933 offering



- Up to 16GB (8GB soldered + 8GB SO-DIMM) DDR4-3200 offering
- Up to 24GB (8GB soldered + 16GB SO-DIMM) DDR4-3200 offering

### **Memory Slots**

One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

### Memory Type\*\*

- DDR4-2933
- DDR4-3200

#### Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

# **Storage**

# Storage Support[1]

- Models with 38Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
  - 2.5" HDD up to 1TB
  - M.2 2242 SSD up to 1TB
- Models with 45Wh battery: one drive, 1x M.2 SSD
  - M.2 2242 SSD up to 1TB

# Storage Slot

- Models with 38Wh battery: one 2.5" drive slot + one M.2 slot
  - One 2.5" SATA HDD slot
  - One M.2 2280 PCle® 4.0 x4 slot
- Models with 45Wh battery: one M.2 slot
  - One M.2 2280 PCIe® 4.0 x4 slot

#### Storage Type\*\*\*

Disk Type	Interface	RPM	Offering
2.5" SATA HDD	SATA 6Gb/s	5.4K	1TB
M.2 2242 SSD	PCle® NVMe®, PCle® 3.0 x4	-	128GB
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	-	256GB / 512GB / 1TB

### Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

# **Removable Storage**

### Card Reader

No card reader

# Multi-Media

### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

### **Speakers**

Stereo speakers, 1.5W x2, Dolby Audio™

### Microphone

Dual-microphone array

### Camera

HD 720p, with privacy shutter, fixed focus

# **Battery**

### Battery\*\*

- 38Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)
- 45Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

### Max Battery Life[1]

 Models with 38Wh battery: MobileMark® 2018: 6.4 hr

# Lenovo V15 G4 IRU



Local video (1080p) playback@150nits: 7.5 hr

Models with 45Wh battery: MobileMark® 2018: 6.8 hr

Local video (1080p) playback@150nits: 8.4 hr

#### Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## **Power Adapter**

### Power Adapter\*\*[1]

- 65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 65W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

### **DESIGN**

### **Display**

#### Display\*\*

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
15.6"	FHD (1920x1080)	None	TN	250nits	Anti- glare	16:9	500:1	45% NTSC	60Hz	45° / 45° / 15° / 35°	TÜV Low Blue Light (Software)
15.6"	FHD (1920x1080)	None	IPS <sup>[1]</sup>	300nits	Anti- glare	16:9	800:1	45% NTSC	60Hz	85° / 85° / 85° / 85°	TÜV Low Blue Light (Software)

### Touchscreen

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

### **Input Device**

#### Pen

No support

### Keyboard

6-row, spill-resistant, multimedia Fn keys, SMB Service Hot key, numeric keypad

# **Keyboard Backlight**

Non-backlight

#### **Touchpad**

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 62 x 104 mm (2.44 x 4.09 inches)

### Mechanical

### Dimensions (WxDxH)[1]

359.2 x 235.8 x 19.9 mm (14.14 x 9.28 x 0.78 inches)

#### Weight<sup>[2]</sup>

Starting at 1.65 kg (3.64 lbs)

Case Color\*\*

# Lenovo V15 G4 IRU



- · Business black
- Iron grey

### Surface Treatment\*\*

- IMR (in-mold decoration by roller)
- Texture

#### Case Material

PC-ABS (top), PC-ABS (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

### CONNECTIVITY

### **Network**

#### WLAN + Bluetooth®\*\*

- Wi-Fi® 5, 802.11ac 2x2 Wi-Fi® + Bluetooth® 5.1, M.2 Card
- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card[1]

### **WWAN**

No support

#### **Ethernet**

Gigabit Ethernet, 1x RJ-45

### Notes:

[1] Wi-Fi® 6 full features might be limited by country-level restrictions.

### **Ports**<sup>[1]</sup>

### **Standard Ports**

- 1x USB 2.0
- 1x USB 3.2 Gen 1
- 1x USB-C<sup>®</sup> 3.2 Gen 1 (support data transfer, Power Delivery (20V only) and DisplayPort™ 1.2)
- 1x HDMI® 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Power connector

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

# **Docking**

### Docking

Various docking solutions supported via USB-C<sup>®</sup>.

For more compatible docking solutions, please visit <u>Docking for Lenovo® V15 G4 IRU</u>

# **SECURITY & PRIVACY**

# **Security**



### **Security Chip**

Firmware TPM 2.0 integrated in SoC

### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

#### **Fingerprint Reader**

No fingerprint reader

### **BIOS Security**

- · Hard disk password
- · Power-on password
- · Supervisor password
- Self-healing BIOS

#### **Other Security**

Camera privacy shutter

# **SERVICE**

# Warranty

#### Base Warranty\*\*

- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service
- No base warranty

# **ACCESSORIES**

### **Bundled Accessories**

### Bundled Accessories[1]

- Lenovo® 15.6" laptop casual toploader, polyester[2]
- None

### Notes:

[1] For more compatible accessory solutions, please visit Accessories for Lenovo® V15 G4 IRU.

[2] Lenovo® 15.6" laptop casual toploader is exclusively available to EMEA.

# OPERATING REQUIREMENTS

# **Operating Environment**

#### Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

#### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### **Altitude**

Maximum altitude (without pressurization): 3048 m (10,000 ft)

#### Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# **CERTIFICATIONS**

# Green Certifications<sup>[1]</sup>



#### Green Certifications[2][3]

- ENERGY STAR® 8.0
- EPEAT™ Silver Registered<sup>[4]</sup>
- ErP Lot 6/26
- FSC certified package
- RoHS compliant

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

- [3] EPEAT™ is only available for MT 83CC.
- [4] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

#### **Other Certifications**

### Mil-Spec Test

MIL-STD-810H military test passed

#### Other Certifications

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with \*\* means that only one option listed under the feature can be configured on selected models.

  Please refer to the model configuration for specific information.
- Feature with \*\*\* means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







intel.





intel





intel.

intel

intel.