


OVERVIEW



1. Kensington Security Slot	6. USB 3.2 Gen 1
2. Power connector	7. USB 3.2 Gen 1
3. Audio-out (3.5mm)	8. USB 3.2 Gen 1
4. HDMI 1.4	9. USB-C 3.2 Gen 1
5. USB 3.2 Gen 1	



PERFORMANCE

Panel

Panel

3-side NearEdgeless, In-Plane Switching

Backlight

WLED

Display Size

23.8 inches

Max View Area

Active Area: 527.0 x 296.5 mm

Resolution

1920 x 1080

Aspect Ratio

16:9

Pixel Pitch

0.275 x 0.275 mm

Dot / Pixel Per Inch

93 dpi

Brightness

250 cd/m²

Contrast Ratio

- Contrast Ratio: 1300:1
- Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 4 msNormal Mode: 6 ms

Off Mode: 14 ms

Refresh Rate

100Hz (HDMI® only)

Color Gamut

Coverage Ratio: 99% sRGBColor Area Ratio: 110% sRGB

Color Support

16.7 Million

Color Depth

8-bit (6-bit+FRC)

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support

Multi-Media

Camera

No bundled webcam (Support Lenovo® LC 50 Monitor Webcam, sold separately)

Microphone

No microphone



Speakers

Integrated Speakers, 3W x2

Power Supply

Power Consumption

- Typical / Max: 15W / 124W
- Sleep / Off mode: <0.5W
- Switch-off Mode: <0.3W
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- AMD FreeSync™
 - AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.
- Lenovo® Artery (Lenovo® Accessories and Display Manager) Support
 Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
 Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- Brightness Calibration
- · Natural Low Blue Light
- Smart Power

The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

Ultraslim

DESIGN

Mechanical

Bezel Width

- Side: 2mm
- Top / Bottom: 2mm / 22mm

Cable Management

Support

Case Color

Cloud grey

Dimensions (WxDxH)[1]

Models	Dimensions
Head Only	539.4 x 43 x 326.2 mm (21.24 x 1.69 x 12.84 inches)
Highest Position	539.4 x 196.2 x 531.1mm (21.24 x 7.72 x 20.91 inches)
Lowest Position	539.4 x 196.2 x 381.1mm (21.24 x 7.72 x 15.00 inches)

Packaging Dimensions (WxDxH)

590 x 138 x 419 mm (23.23 x 5.43 x 16.50 inches)

Weight^[2]

Models	Weight
Monitor With Stand	5.2 kg (11.5 lbs)
Monitor Head Only	3.4 kg (7.5 lbs)

Packaging Weight

7.2 kg (15.9 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +22° tilt, left & right 360° swivel, -90° to +90° pivot, up to 150mm lift



In the Box

- · Monitor with stand
- 1x USB-C[®] to USB-C[®] cable (1.8m)
- 1x Power cable (1.8m)
- Quick setup guide
- · Warranty booklet

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports^[2]

- 1x USB-C® 3.2 Gen 1 (DP 1.2 Alt Mode and up to 75W PD), USB upstream
- 4x USB 3.2 Gen 1, USB downstream
- 1x HDMI® 1.4
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Up to 75W power delivery to compatible devices by USB-C®. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™ (2.5 mm x 6 mm)

SERVICE

Warranty

Base Warranty

- 1-year courier or carry-in service
- 3-year limited warranty

CERTIFICATIONS

Green Certifications

- EU Energy Label (E-class)
- RoHS compliant
- Volatile Organic Compound Certification



Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

Other Certifications

Other Certifications

- Evesafe® Certified 2.0
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













