


# **OVERVIEW**



1. Nano-SIM card slot *	6. HDMI
2. USB-C 3.2 Gen 2	7. USB 3.2 Gen 1 (Always On)
3. USB 3.2 Gen 1	8. USB-C 3.2 Gen 2
4. Headphone / microphone combo jack (3.5mm)	9. Kensington Nano Security Slot
5. Pen slot *	10. Smart card reader *

### Notes:

• Items with \* are only available on selected models



# **PERFORMANCE**

## **Processor**

## **Processor Family**

AMD Ryzen<sup>™</sup> 3 / 5 / 7 Processor

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 3 5425U	4	8	2.7GHz	4.1GHz	2MB L2 / 8MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 5 5625U <sup>[1]</sup>	6	12	2.3GHz	4.3GHz	3MB L2 / 16MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 5 PRO 5675U	6	12	2.3GHz	4.3GHz	3MB L2 / 16MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 7 5825U[2]	8	16	2.0GHz	4.5GHz	4MB L2 / 16MB L3	AMD Radeon™ Graphics
AMD Ryzen™ 7 PRO 5875U	8	16	2.0GHz	4.5GHz	4MB L2 / 16MB L3	AMD Radeon™ Graphics

### Notes:

- [1] AMD Ryzen™ 5 5625U is for special bid in EMEA.
- [2] AMD Ryzen™ 7 5825U is for special bid in EMEA.

# **Operating System**

# Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64<sup>[1]</sup>
- Ubuntu Linux<sup>[2]</sup>
- · No operating system

### Notes:

- [1] Windows® 11 DG Windows® 10 Pro 64 is for special bid only.
- [2] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

# **Graphics**

## **Graphics**

Graphics	Type	Memory	TGP	Key Features
AMD Radeon™ Graphics	Integrated	Shared	Share CPU TDP	DirectX® 12

# **Monitor Support**

## **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 3840x2160@60Hz
- USB-C® supports up to 5120x2880@60Hz

# **Chipset**

# Chipset

AMD SoC (System on Chip) platform

## Memory

# **Max Memory**

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

### **Memory Slots**

Memory soldered to systemboard, no slots, dual-channel

# **Memory Type**



DDR4-3200

# **Storage**

Storage Support[1]

One drive, up to 1TB M.2 2242 SSD

**Storage Slot** 

One M.2 2242 PCIe® 3.0 x4 slot

Storage Type<sup>[2]</sup>

Disk Type	Interface	Offering	Security
M.2 2242 SSD	PCle® NVMe®, PCle® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0

Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] The SSD with PCle® 4.0x4 is downgraded to closer to PCle® 3.0x4 due to AMD platform limitations.

# **Removable Storage**

## **Optical**

None

### **Card Reader**

No card reader

## Multi-Media

### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### **Speakers**

Stereo speakers, 2W x2, Dolby® Audio™

# Microphone

Dual-microphone array, far-field, Dolby® Voice

# Camera\*\*

- Front FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- Front FHD 1080p + IR hybrid, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus
- Front FHD 1080p, with privacy shutter, fixed focus
- Front FHD 1080p, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus
- Front HD 720p, with privacy shutter, fixed focus
- Front HD 720p, with privacy shutter, fixed focus; rear 5.0-megapixel, autofocus

# **Battery**

## **Battery**

Integrated Li-Polymer 46Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

## Battery Life[1]

Configuration 1 (max battery life)

MobileMark® 2018: up to 9.8 hr with 628 performance score @200nits

JEITA 2.0: up to 11.7 hr @150nits

Local video playback: up to 11.5 hr @150nits

Alternate configuration 2

MobileMark® 2018: up to 9.7 hr with 623 performance score @200nits

JEITA 2.0: up to 12.1 hr @150nits

Local video playback: up to 12.1 hr @150nits

Alternate configuration 3

MobileMark® 2018: up to 9.4 hr with 590 performance score @200nits

JEITA 2.0: up to 12.5 hr @150nits

Local video playback: up to 12.5 hr @150nits

Notes:

# ThinkPad L13 Yoga Gen 3 (AMD)



[1] Configuration 1 (max battery life): WUXGA (touch), AMD Ryzen™ 7 PRO 5875U, 16GB DDR4, Win 11, 46Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA (touch), AMD Ryzen™ 5 5625U, 16GB DDR4, Win 11, 46Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (touch), AMD Ryzen™ 3 5425U, 8GB DDR4, Win 11, 46Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

# **Power Adapter**

# Power Adapter\*\*[1]

- 45W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz<sup>[2]</sup>
- 45W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz<sup>[3]</sup>
- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz<sup>[4]</sup>
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz<sup>[5]</sup>

#### Notes:

[1] AC adapter offerings depend on the country.

[2], [3] 45W USB-C® AC adapter is NOT available in EMEA.

[4], [5] 65W USB-C® slim AC adapter is NOT available in EMEA.

# **DESIGN**

# **Display**

## Display\*\*[1]

Si	ze	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)	Key Features
13.	۲" I	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- reflection, anti-smudge	16:10	1000:1	100% sRGB	85°/85°/85°/85°	-
13.	.3"	WUXGA (1920x1200)	Multi- touch	IPS	500nits	Anti-glare, anti-smudge	16:10	1000:1	72% NTSC	85°/85°/85°/85°	ThinkPad® Privacy Guard

### Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

### Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

# Multi-mode

## Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

## **Input Device**

### Pon

- Lenovo® Integrated Pen, with built-in rechargeable battery, 4096 levels of pressure sensitivity, on-board garaged and rechargeable
- No pen<sup>[1]</sup>

### Keyboard

# ThinkPad L13 Yoga Gen 3 (AMD)



6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

### **Keyboard Backlight**

- LED backlight
- · Non-backlight

## UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 56 x 115 mm (2.24 x 4.53 inches)

#### Notes:

[1] Customer needs to purchase an external pen separately.

### Mechanical

## Dimensions (WxDxH)[1]

305 x 218 x 17.1 mm (12.0 x 8.58 x 0.67 inches)

### Weight<sup>[2]</sup>

Starting at 1.31 kg (2.89 lbs)

### Case Color\*\*

- Storm grey
- Thunder black

## **Case Material**

Aluminium (top), GFRP (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# **CONNECTIVITY**

# **Network**

### Ethernet[1]

No onboard Ethernet

### WLAN + Bluetooth®\*\*[2][3]

- Qualcomm<sup>®</sup> Wi-Fi<sup>®</sup> 6E NFA725A, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.1<sup>[4]</sup>
- AMD Wi-Fi® 6E RZ616, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.1

### WWAN\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM05-G, 4G LTE CAT4, M.2 card
- Fibocom L860-GL-16, 4G LTE CAT16, M.2 card<sup>[5]</sup>
- No support

## SIM Card

- Gemalto eSIM card (physical)
- No physical SIM card inbox

## **NFC**

- · Near Field Communication
- No support

## Notes:

- [1] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.
- [2] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.
- [3] Wi-Fi® 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.



- [4] Qualcomm® NFA-725A is for special bid only in EMEA.
- [5] CAT16 is NOT available in EMEA.

### Ports<sup>[1]</sup>

## **Standard Ports**

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x USB-C® 3.2 Gen 2 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

# Optional Ports\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

# **Docking**

### **Docking**

Various docking solutions supported via USB-C<sup>®</sup>.

For more compatible docking solutions, please visit Docking for ThinkPad® L13 Yoga® Gen 3 (AMD)

## **Monitor Cable**

### Monitor Cable\*\*\*

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to VGA Adapter
- Lenovo® USB-C® to HDMI® Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- No monitor cable

# **SECURITY & PRIVACY**

## **Security**

## **Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

## **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

### **Smart Card Reader**

- Smart card reader
- · No smart card reader

## **Fingerprint Reader**

- Touch style fingerprint reader integrated in power button, match-on-chip
- · No fingerprint reader

## **BIOS Security**

- · Power-on password
- Supervisor password
- NVMe® password
- Self-healing BIOS

## **Other Security**

# ThinkPad L13 Yoga Gen 3 (AMD)



- · Camera privacy shutter
- (Optional) Privacy Guard with Privacy Alert
- Glance by Mirametrix®
- (Optional) IR camera for Windows® Hello (facial recognition)

## MANAGEABILITY

# **System Management**

## **System Management**

- DASH
- Non-DASH

## **SERVICE**

# **Warranty**

## Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service

# **ENVIRONMENTAL**

# Sustainability

## Material

50% PCC recycled plastic used in speaker enclosure 30% PCC recycled plastic used in the battery

95% PCC recycled plastic used in standard 65W adapter

Low-temperature solder

90% recycled and/or sustainable packaging

## Operating Environment

## Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

### **Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

### Δltitudo

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# **ACCESSORIES**

# **Bundled Accessories**

# **Bundled Accessories**\*\*\*[1]

- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to USB-A Adapter
- Lenovo® USB-C® to USB-C® Cable 2m
- None

Notes:



[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® L13 Yoga® Gen 3 (AMD)

# **CERTIFICATIONS**

## Green Certifications<sup>11</sup>

### **Green Certifications**[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 3
- · RoHS compliant
- TCO Certified 9.0

### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please see epeat.net for registration status by country.

# **Other Certifications**

### Mil-Spec Test

MIL-STD-810H military test passed

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMDZI AMDZI



AMD



ДФМА





AMDA