
# **OVERVIEW**



1. Nano-SIM card slot *	7. SD Express 7.0 card reader
2. Headphone jack (3.5mm)	8. Smart card reader *
3. USB 3.2 Gen 1 (Always On)	9. USB4
4. USB 3.2 Gen 1	10. USB4
5. Kensington Nano Security Slot	11. Power-in (Slim Tip)
6. HDMI	

Notes:

• Items with \* are only available on selected models

# PERFORMANCE

## Processor

## **Processor Family**

Up to AMD Ryzen<sup>™</sup> PRO 7040HS Series Processor, supports up to 8 cores, up to 5.2GHz

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 5 PRO 7640HS	6	12	4.3GHz	5.0GHz	6MB L2 / 16MB L3	AMD Radeon™ 760M
AMD Ryzen™ 7 7840HS	8	16	3.8GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M
AMD Ryzen™ 7 PRO 7840HS	8	16	3.8GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M
AMD Ryzen™ 9 PRO 7940HS	8	16	4.0GHz	5.2GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M

# **Operating System**

## **Operating System**\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows<sup>®</sup> 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Ubuntu Linux LTS
- Red Hat Enterprise Linux 9.2 (certified only, for detailed and latest information, please visit Red Hat Certified Hardware)<sup>[1]</sup>
- No preload operating system

#### Notes:

[1] Red Hat Enterprise Linux 9.2 certification will be available after Nov 30, 2023.

# Graphics

## Graphics

Graphics	Туре	Memory	TGP	Key Features
AMD Radeon™ 760M	Integrated	Shared	Share CPU TDP	DirectX® 12
AMD Radeon™ 780M	Integrated	Shared	Share CPU TDP	DirectX® 12
NVIDIA® RTX 2000 Ada Generation Laptop GPU	Discrete	8GB GDDR6	35W	DirectX® 12 Ultimate, Vulkan Support, NVIDIA® FXAA / TXAA Anti-Aliasing, NVIDIA® RTX Desktop Manager
NVIDIA® RTX A1000 Laptop GPU	Discrete	6GB GDDR6	35W	DirectX® 12 Ultimate, Vulkan Support, NVIDIA® FXAA / TXAA Anti-Aliasing, NVIDIA® RTX Desktop Manager
NVIDIA® RTX A500 Laptop GPU	Discrete	4GB GDDR6	35W	DirectX® 12 Ultimate, Vulkan Support, NVIDIA® FXAA / TXAA Anti-Aliasing, NVIDIA® RTX Desktop Manager

# **Monitor Support**

## **Monitor Support**

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB4®)

• HDMI® supports up to 7680x4320@60Hz

• USB4® supports up to 5120x3200@60Hz (USB-C® to DP)

# Chipset

## Chipset

AMD SoC (System on Chip) platform

# Memory

Max Memory

Up to 64GB (2x 32GB DDR5 SO-DIMM)

Two DDR5 SO-DIMM slots, dual-channel capable

## Memory Type

DDR5-5600 non-ECC, maximum transfer speeds of up to 5600 MT/s

# Storage

### Storage Support<sup>[1]</sup>

Up to two drives, 2x M.2 SSD • M.2 2280 SSD up to 4TB, 2TB each

Storage Slot

Two M.2 2280 PCIe® 4.0 x4 slots

#### Storage Type

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

# **Removable Storage**

#### Card Reader

SD Express 7.0 card reader

# Multi-Media

## Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

#### Speakers

Stereo speakers, 2W x2, Dolby Audio™

#### Microphone

- Dual-microphone array, far-field, Dolby Voice®
- No microphone

#### Camera\*\*

- FHD 1080p with privacy shutter, fixed focus
- 5.0MP + IR with privacy shutter and Ultrasonic Human Presence Detection, fixed focus
- No camera

# Battery

## Battery

90Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

## **Power Adapter**

#### Power Adapter\*\*[1]

- 135W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

# DESIGN

# Display

## Display\*\*[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	-	Key Features
------	------------	-------	------	------------	---------	-----------------	-------------------	----------------	---	--------------

Lenovo PSREF Product Specifications Reference

									(L/R/U/D)	
16″	WUXGA (1920x1200)	None	IPS	300nits	Anti- glare	16:10	800:1	45% NTSC	85° / 85° / 85° / 85°	83.9% screen to body ratio, DC dimming
16″	WUXGA (1920x1200)	None	IPS	300nits	Anti- glare	16:10	1200:1	100% sRGB	85° / 85° / 85° / 85°	TÜV Low Blue Light, 83.9% screen to body ratio, DC dimming
16″	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- glare	16:10	800:1	45% NTSC	85° / 85° / 85° / 85°	83.9% screen to body ratio, DC dimming
16″	WQUXGA (3840x2400)	None	IPS	800nits	Anti- glare	16:10	1500:1	100% DCI-P3	85° / 85° / 85° / 85°	DisplayHDR <sup>™</sup> 400, Dolby Vision®, Eyesafe® Certified 2.0, TÜV Low Blue Light, X-Rite® Factory Color Calibration, 83.9% screen to body ratio, DC dimming

#### Color Calibration

• X-Rite<sup>®</sup> factory color calibration (WQUXGA display)

• No color calibration

#### Touchscreen

- On-cell multi-touch, supports 10-point touch (selected FHD display)
- Non-touch

#### Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## **Input Device**

#### Pen

No support

#### Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

#### Keyboard Backlight

LED backlight

#### UltraNav™

3-button TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 67.6 x 115 mm (2.66 x 4.53 inches)

## **Mechanical**

#### Dimensions (WxDxH)[1]

365 x 262 x 24.66 mm (14.37 x 10.32 x 0.97 inches)

#### Weight<sup>[2]</sup>

Starting at 2.2 kg (4.85 lbs)

#### **Case Color**

Thunder black

#### **Case Material**

PC-ABS (top), PC-ABS (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

# Network

## WLAN + Bluetooth®

Qualcomm<sup>®</sup> Wi-Fi<sup>®</sup> 6E NFA725A, 802.11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.3<sup>[1]</sup>

## WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- · Fibocom L860-GL-16, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- No support

#### SIM Card

No physical SIM card inbox

#### Ethernet

No onboard Ethernet

#### NFC

- Near Field Communication
- No support

#### Notes:

[1] Wi-Fi<sup>®</sup> 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-

Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information</u> <u>on Microsoft®</u>.

## **Ports**<sup>III</sup>

## **Standard Ports**

- 2x USB 3.2 Gen 1 (one Always On)
- 2x USB4<sup>®</sup> 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort<sup>™</sup> 1.4)<sup>[2]</sup>
- 1x HDMI<sup>®</sup> 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x SD Express 7.0 card reader
- 1x Security keyhole

## **Optional Ports**

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Power Delivery only supports power-out for charging peripherals.

# Docking

## Docking

Various docking solutions supported via Thunderbolt™ or USB-C<sup>®</sup>. For more compatible docking solutions, please visit <u>Docking for ThinkPad<sup>®</sup> P16v Gen 1 (AMD)</u>

# **SECURITY & PRIVACY**

# Security

Security Chip

Lenovo

Discrete TPM 2.0 (TCG certified) and Microsoft® Pluton TPM 2.0, one enabled at one time

#### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

#### Smart Card Reader

- Smart card reader
- No smart card reader

## Fingerprint Reader

Touch style fingerprint reader integrated in power button, match-on-chip

#### BIOS Security

- NVMe<sup>®</sup> password
- Power-on password
- Supervisor password
- Self-healing BIOS

#### **Other Security**

- Bottom cover tamper detection
- Camera privacy shutter (camera models)
- (Optional) Ultrasonic Human Presence Detection for IR camera
- (Optional) IR camera for Windows® Hello (facial recognition)

# MANAGEABILITY

## System Management

#### System Management

- AMD PRO Manageability
- Non-DASH

# SERVICE

# Warranty

#### **Base Warranty\*\***

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

# ACCESSORIES

# **Bundled Accessories**

#### Bundled Accessories\*\*\*[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo<sup>®</sup> USB-C<sup>®</sup> to DisplayPort<sup>™</sup> Adapter
- Lenovo<sup>®</sup> USB-C<sup>®</sup> to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter

#### Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® P16v Gen 1 (AMD)

# **OPERATING REQUIREMENTS**

# **Operating Environment**

### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)

# ThinkPad P16v Gen 1 (AMD)

Lenovo

- Storage without package:  $5^\circ\text{C}$  (41°F) to 43°C (109°F)

### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# **ENVIRONMENTAL**

## Sustainability

#### Material<sup>[1]</sup>

85% PCC recycled plastic used in key caps 90% PCC recycled plastic used in speaker enclosure 90% PCC recycled plastic used in the battery 30% PCC recycled plastic used in 135W and 170W adapters 90% recycled and/or sustainable packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

# CERTIFICATIONS

## **Green Certifications**<sup>11</sup>

## Green Certifications<sup>[2]</sup>

- ENERGY STAR<sup>®</sup> 8.0
- EPEAT<sup>™</sup> Gold Registered<sup>[3]</sup>
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.

[2] EPEAT<sup>™</sup> registration and ENERGY STAR<sup>®</sup> certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT<sup>™</sup> is registered where applicable, please visit <u>epeat.net</u> for registration status by country.

# **Other Certifications**

## Mil-Spec Test

MIL-STD-810H military test passed

#### Other Certifications

- (Optional) Eyesafe® Certified
- (Optional) TÜV Rheinland® Low Blue Light

# **ISV Certifications**

## **ISV Certifications**

Please visit ISV certifications for Lenovo® Workstations

- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with \*\*\* means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"

WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.







