

OVERVIEW



1. Power connector	8. Ethernet (RJ-45)
2. HDMI 2.1 TMDS	9. USB 3.2 Gen 2
3. HDMI 2.1 TMDS	10. USB 3.2 Gen 2
4. DisplayPort 1.4	11. Audio-out (3.5mm)
5. DisplayPort 1.4 out	12. USB-C 3.2 Gen 2
6. USB4 40Gbps	13. USB 3.2 Gen 2
7. USB-C 3.2 Gen 2	14. USB 3.2 Gen 2



PERFORMANCE

Panel

Panel

3-side NearEdgeless, In-Plane Switching

Backlight

Mini-LED

Display Size

27 inches

Max View Area

• Active Area: 596.7 x 335.6 mm

• Scree Dimension: 608.9 x 359.8 mm

Resolution

3840 x 2160

Aspect Ratio

16:9

Pixel Pitch

0.155 x 0.155 mm

Dot / Pixel Per Inch

163 dpi

Brightness

Peak: 1200 cd/m²
Typical: 650 cd/m²

Contrast Ratio

• Contrast Ratio: 1000:1

• Dynamic Contrast Ratio (Typical): 3000000:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 4 msNormal Mode: 6 ms

Refresh Rate

60Hz

Color Gamut

- 100% sRGB
- 99% DCI-P3
- 100% BT.709
- 81% BT.2020
- 99% Adobe® RGB

Color Support

1.07 Billion

Color Depth

10-bit (8-bit+FRC)

Screen Surface Treatment

Anti-alare

Curvature

Flat Panel

Operating System

Operating System

- Windows® 11 Support
- Windows® 10 Support



Multi-Media

Camera

Optional Modular Camera Support

Microphone

No microphone

Speakers

Optional Modular Soundbar support

Power Supply

Power Consumption

- Typical / Max: 26W / 315W
- Sleep / Off mode: <0.5W / <0.3W
- Switch-off Mode: <0.3W
- Energy Star Power On: 26W
- Energy Star TEC: 82.6kWh
- Internal Power Supply

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- HDR10 Compliance
- DisplayHDR[™] 1000
- Factory Calibration: Avg. Delta E<1.5
- Picture In Picture (PIP) / Picture By Picture (PBP) Support
- Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems). Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center.
- HLG
- KVM Switch
- Smart Power

The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

• Smart Sensor (Ambient Light Sensor, Human Detection Sensor)

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre® M Series Tiny, ThinkCentre® M Series Nano

For supporting Tiny / Nano devices, additional Clamp Bracket Mounting Kit III (PN: 4XF1K72399) is needed (sold separately).

Bezel Width

- · Side: 2mm
- Top / Bottom: 2mm / 27.1mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)[1]

Models	Dimensions
Head Only	613.5 x 76.4 x 372.9 mm (24.15 x 3.01 x 14.68 inches)
Highest Position	613.5 x 220.4 x 549.8 mm (24.15 x 8.68 x 21.65 inches)
Lowest Position	613.5 x 220.4 x 397.8 mm (24.15 x 8.68 x 15.66 inches)



Packaging Dimensions (WxDxH)

706 x 163 x 504 mm (27.8 x 6.41 x 19.84 inches)

Weight^[2]

Models	Weight
Monitor With Stand	8.8 kg (19.4 lbs)
Monitor Head Only	6.2 kg (13.7 lbs)

Packaging Weight

12 kg (26.5 lbs)

Mounting

Supports VESA mount 100 x 100 mm

Stand

Supports -5° to +23.5° tilt, left & right 45 swivel, 90° pivot, up to 155mm lift

In the Box

- · Monitor with stand
- 1x DP cable (1.8m) (for US, Canada only)
- 1x USB-C® to USB-A gen 2 cable (1m)
- 1x USB4® cable (1m)
- 1x Power cable (1.8m)
- Factory calibration report
- Quick setup guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

Support 10M / 100M / 1000M

Ports^[1]

Rear Ports

- 1x USB-C® 3.2 Gen 2 (support data transfer, up to 15W PD), USB downstream
- 1x USB-C® 3.2 Gen 2. USB upstream
- 1x USB4® 40Gbps (support data transfer, DP 1.4 Alt Mode and up to 140W PD), USB upstream
- 4x USB 3.2 Gen 2 (1x BC 1.2), USB downstream
- 1x DisplayPort[™] 1.4
- 1x DisplayPort™ 1.4 (Out)
- 1x Ethernet (RJ-45)
- 1x audio-out (3.5mm)
- 2x HDMI® 2.1 TMDS, supports 3840x2160@60 Hz

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

SECURITY & PRIVACY



Security

Physical Locks

Kensington® Security Slot™ (2.5 mm x 6 mm and 3 mm x 7 mm)

SERVICE

Warranty

Base Warranty

3-year limited warranty

CERTIFICATIONS

Green Certifications

- ENERGY STAR® Certified
- EPEAT™ Gold Registered
- EU Energy Label (F-class)
- RoHS compliant
- Volatile Organic Compound Certification

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit https://compliance.lenovo.com.

Other Certifications

Other Certifications

- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Flicker Free
- TÜV Rheinland® Low Blue Light
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













