# **OVERVIEW**



1. SD card reader	5. HDMI					
2. USB-A (USB 5Gbps)	6. USB-C (USB 10Gbps), with USB PD 3.0 & DP 1.4					
3. USB-A (USB 5Gbps), Always On	7. Headphone / microphone combo jack (3.5mm)					
4. Power connector *						

Notes:

• Items with \* are only available on selected models

• USB-C Hi-Speed (USB-C 2.0), with Power Delivery 3.0 is for UMA model only and mutually exclusive with Power connector port (not shown on the sample product above)

# PERFORMANCE

## Processor

### Processor Family

AMD Ryzen<sup>™</sup> 5 / 7 Processor

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
AMD Ryzen™ 5 6600HS Creator Edition	6	12	3.3GHz	4.5GHz	3MB L2 / 16MB L3	AMD Radeon™ 660M Graphics
AMD Ryzen™ 7 6800HS Creator Edition	8	16	3.2GHz	4.7GHz	4MB L2 / 16MB L3	AMD Radeon™ 680M Graphics

# **Operating System**

### **Operating System**\*\*

- Windows<sup>®</sup> 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

# Graphics

### Graphics\*\*

Graphics	Туре	Memory	Key Features
AMD Radeon™ 680M	Integrated	Shared	DirectX® 12
NVIDIA® GeForce RTX™ 3050 Laptop GPU	Discrete	4GB GDDR6	Dynamic Boost 2.0, NVIDIA® DLSS, DirectX® 12 Ultimate

# **Monitor Support**

### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI<sup>®</sup> supports up to 4096x2160@60Hz
- USB-C<sup>®</sup> supports up to 5120x3200@60Hz

# Chipset

### Chipset

AMD SoC (System on Chip) platform

### Memory

### Max Memory

16GB soldered memory, not upgradable

### Memory Slots

Memory soldered to systemboard, no slots, dual-channel

### **Memory Type**

LPDDR5-6400

### Storage

### Storage Support<sup>[1]</sup>

One drive, up to 1TB M.2 2280 SSD

### Storage Slot

One M.2 2280 PCIe<sup>®</sup> 4.0 x4 slot

### Storage Type

Disk Type	Interface	Offering		
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB		

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo<sup>®</sup> storage offerings.

# Removable Storage

### Card Reader

SD card reader

## **Multi-Media**

### Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

### Speakers

Stereo speakers, 2W x2, optimized with Dolby Atmos®

### Microphone

Dual-microphone array

### Camera

FHD 1080p + IR, fixed focus, with ToF sensor

### Sensor

### Sensors

- Hall sensor
- ToF sensor

## **Battery**

### Battery

Integrated Li-Polymer 75Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[1]

### Max Battery Life<sup>[2]</sup>

- Models with discrete graphics (display@165Hz): MobileMark® 2018@200nits: 10.8 hr
- Local video (1080p) playback@150nits: 15.9 hr
  Models with discrete graphics (display@60Hz): MobileMark<sup>®</sup> 2018@200nits: 9.2 hr
- Local video (1080p) playback@150nits: 13.7 hr
  Models with integrated graphics (display@165Hz): MobileMark<sup>®</sup> 2018@200nits: 13 hr
  Local video (1080p) playback@150nits: 18.8 hr
- Models with integrated graphics (display@60Hz): MobileMark<sup>®</sup> 2018@200nits: 15 hr Local video (1080p) playback@150nits: 20.8 hr

### Notes:

[1] Rapid Charge Boost is only effective in hibernates or fully shutting down the computer.

[2] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## **Power Adapter**

### Power Adapter\*\*[1]

- 100W USB-C<sup>®</sup> slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 135W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

## Notes:

[1] AC adapter offerings depend on the country.

# DESIGN

# Display

### Display<sup>[1]</sup>

S	ize	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
1		2.5K (2560x1600)	Multi- touch	IPS	500nits	Glossy, anti- fingerprint	16:10	1,200:1	100% sRGB	165Hz (Max)	89°/89°/89°/89°	AAR 92%, Eyesafe® Certified, Dolby Vision®, VESA DisplayHDR™ 400

### Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## **Input Device**

### Keyboard

6-row, multimedia Fn keys, numeric keypad

### Keyboard Backlight

LED backlight

### Touchpad

Buttonless glass surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

## **Mechanical**

### Dimensions (WxDxH)<sup>[1]</sup>

356.81 x 247.42 x 17.4 mm (14.05 x 9.74 x 0.69 inches)

### Weight<sup>[2]</sup>

Starting at 2.08 kg (4.59 lbs)

### Case Color

Storm grey

### Surface Treatment

Aluminium stamping (anodized)

### Case Material

Aluminium (top), aluminium (bottom)

### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo<sup>®</sup> lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

# Network

Ethernet No onboard Ethernet

WLAN + Bluetooth®[1][2]

Wi-Fi $^{\rm e}$  6, 802.11ax 2x2 Wi-Fi $^{\rm e}$  + Bluetooth $^{\rm e}$  5.1, M.2 card

Notes:

Lenovo

[1] Bluetooth<sup>®</sup> may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi<sup>®</sup> 6 full features might be limited by country-level restrictions.

### **Ports**<sup>(1)</sup>

### **Standard Ports**

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C<sup>®</sup> (USB 10Gbps / USB 3.2 Gen 2), with USB PD 3.0 and DisplayPort<sup>™</sup> 1.4
- 1x HDMI® 2.0
- 1x Headphone / microphone combo jack (3.5mm)
- 1x SD card reader

#### **Optional Ports**\*\*

- 1x USB-C<sup>®</sup> (Hi-Speed USB / USB 2.0), with USB PD 3.0 (models with integrated graphics)
- 1x Power connector (models with discrete graphics)

#### Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

## Docking

### Docking

Various docking solutions are supported via USB-C<sup>®</sup>. For more compatible docking solutions, please visit <u>Docking for Yoga<sup>®</sup> Slim 7 Pro 16ARH7</u>

# **SECURITY & PRIVACY**

### Security

Security Chip

Firmware TPM 2.0 integrated in SoC

### Fingerprint Reader

No fingerprint reader

### **BIOS Security**

- Administrator password
- User password
- User hard disk password
- Master hard disk password
- Self-healing BIOS

### Other Security

IR camera for Windows® Hello (facial recognition)

# SERVICE

### Warranty

### **Base Warranty\*\***

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

# ACCESSORIES

### **Bundled Accessories**

Bundled Accessories<sup>[1]</sup>

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for Yoga® Slim 7 Pro 16ARH7.

# **OPERATING REQUIREMENTS**

## **Operating Environment**

### Temperature<sup>[1]</sup>

- At altitudes up to 2438 m (8,000 ft)
   Operating: 5°C to 35°C (41°F to 95°F)
- Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

### Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# CERTIFICATIONS

## **Green Certifications**<sup>11</sup>

### Green Certifications<sup>[2]</sup>

- ENERGY STAR<sup>®</sup> 8.0
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.
 [2] EPEAT<sup>™</sup> registration and ENERGY STAR<sup>®</sup> certification are dependent on system OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

## **Other Certifications**

### Other Certifications

- Eyesafe® Certified
- TÜV Rheinland<sup>®</sup> Low Blue Light (Hardware Solution)
- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.











YCGA